

# Leica iCON CC50

## Versatile field controller for tough site conditions



**icon**  
intelligent construction

### Leica iCON CC50 is the perfect controller for any job on site.

The built-in GPS receiver, e-compass, altimeter and 3M pixels auto-focus camera have been smartly integrated to develop an all-in-one solution. It provides high compatibility and flexible connectivity for various construction applications. The embedded 8GB memory ensures extensive data process and storage. The Leica iCON CC50 offers substantially longer battery life, up to 10 hours to provide all-day usage while on site. The high resolution, sunlight-visible VGA display shows images, maps and data in crisp detail.

- State-of-the-art technology
- Very robust, built for use in harsh conditions
- Various communication possibilities (Bluetooth®, WLAN, RS232) for the use with different sensors for different applications
- Long-range Bluetooth® option
- Highly productive positioning work with Leica iCON build and Leica iCON site application software



- when it has to be **right**

**Leica**  
Geosystems

**Leica iCON CC50**  
Lightweight, handy field controller



Specifications	
<b>Operating System</b>	Genuine Windows Mobile® 6.1 Classic
<b>Mobile Computing Processor</b>	Marvell PXA310 806MHZ
<b>Display</b>	3.5" TFT LCD VGA (480 x 640) Transflective sunlight readable display Pressure sensitive touchscreen
<b>Storage &amp; Memory</b>	128MB MDDR 256MB NAND flash and 8GB iNAND
<b>Keypad</b>	Alpha-numeric keypad
<b>I/O Interface</b>	Serial port (9-pin; D-sub) x 1, manual switch by SW with FlexiConn UART interface, USB OTG (client 2.0 and host 1.1; 5-pin; type Mini AB) x 1, Microphone x 1, Speaker x 1, DC in Jack x 1, Docking connector (4-pin) x 1
<b>Communication Interface</b>	WLAN 802.11 b/g, Bluetooth® (v2.0+EDR class 2), GPS (with internal antenna), Optional long-range Bluetooth®
<b>Software</b>	Microsoft Internet Explorer Mobile® Microsoft Office Mobile Applications Microsoft Office Mobile® Microsoft® Windows Media® Player 10 Mobile Microsoft ActiveSync 4.5 for data sync
<b>Power</b>	AC adapter (50W, 100-240VAC; 50/60Hz), Li-Ion smart battery (5600mAh), (up to 10 hours of battery life)*

Specifications	
<b>Dimension (WxDxH) &amp; Weight</b>	8.9 x 3 x 17.8 cm (3.5" x 1.18" x 7.01"), 530 g (18.69 oz)**
<b>Field Service Features</b>	GPS: SIRFstarIII, 3M pixels auto focus camera with LED light, E-compass, Alimeter
<b>GPS Sensor Specification</b>	Chipset: SIRFstarIII, Receiver Type: L1 (C / A), Channels: 20 channels all-in-view tracking, Update Rate: 1 Hz, Horizontal Accuracy: I) Autonomous: 5 m / 16.4 ft, II) DGPS: 1~3m / 3.3~9.8 ft, Cold Start Time: 45 sec average, Warm Start Time: 30 sec average, Hot Start Time: 1 sec average, Reacquisition: 0.1 sec average
<b>Rugged Features</b>	MIL-STD-810G and IP67 certified, Tamper-proof plastic case, Vibration resistant, Drop resistant (26 drops from 1.22m / 4 ft), Tumbling resistant (1,000 cycles; 0.5 m / 1.6 ft)
<b>Environmental Specification</b>	Temperature: Operating: -30°C to 60°C / -22°F to 140°F, Storage: -40°C to 70°C / -40°F to 158°F; Humidity: -95% RH, non-condensing
<b>Alphanumeric Data Entry</b>	Soft input panel (SIP) on screen keyboard, Transcriber handwriting recognition, Alpha-numeric keypad, Nuance XT9 SIP
<b>Certification</b>	CE, FCC, UL/TUV
<b>Inbox Accessory</b>	AC Adapter, USB-Host-Adapter, USB cable, Protection film, Quick start guide, Battery, Stylus, Stylus tether

\* Battery performance will vary with software applications, wireless settings, power management settings, LCD brightness, customised modules and environmental conditions. Battery life and charge cycles vary by use and settings.  
\*\* Weight varies from configurations and optional accessories.



**Leica iCON CC60/61**  
Rugged, mobile tablet PC with enhanced connectivity and functionality.



**Leica iCON gps 60**  
Versatile Smart Antenna for multi-purpose positioning tasks.



**Leica iCON robot 50**  
One-person operation, saving time and increasing productivity when carrying out layout tasks and as-built checks.



**Leica Builder**  
Intuitive, powerful and scalable manual total station series for routine construction tasks on site.



**Total Quality Management - our commitment to total customer satisfaction.**

The **Bluetooth®** word mark and logos are owned by Bluetooth SIG, Inc. and any use of such marks by Leica Geosystems AG is under licence. Windows and Windows CE are a registered trademark of Microsoft Corporation. All other trademarks and trade names are those of their respective owners.

Illustrations, descriptions and technical data are not binding. All rights reserved. Printed in Switzerland - Copyright Leica Geosystems AG, Heerbrugg, Switzerland, 2012. 793588en - II.12 - galledia

**Leica Geosystems AG**  
Heerbrugg, Switzerland  
[www.leica-geosystems.com](http://www.leica-geosystems.com)

- when it has to be **right**

